

# Rotary Screw Compressors

R-Series 5-11 kW (5-15 hp)

Fixed and Variable Speed Drives

## Compact Performance Where You Need It

The affordable Ingersoll Rand R-Series 5-11 kW compressor extends the R-Series family into the commercial machine range as well as offers innovative features and a compact design that fits virtually any application environment.



### Fit-Anywhere Footprint

The vertically-stacked internal components reduce the basic compressor footprint by 20% compared to previous models for both the base and integrated dryer versions.

### A Legacy of Engineered Reliability

Ingersoll Rand has taken the best features from the current R-Series family to deliver the same great performance in the 5-11 kW range. Improved innovations such as a leak-free, next-generation airend, improved seals and a reduced number of components continue to extend our legacy of reliability.

### Convenient, Programmable Control

Ingersoll Rand Xe Series controllers deliver increased control functionality through an intuitive user interface with large navigation buttons for both fixed and variable speed drives.



The Xe-50 (fixed speed) and Xe-70 (variable speed) controllers feature an easy-to-use interface with a high-resolution color display



# Proven Reliability. Robust Design.

The R-Series 5-11 kW family of compressors delivers optimum performance and easier maintenance, all in a robust, innovative package.



Vertically-stacked drive components reduce overall footprint by 20%.

## Compact Productivity

- **Vertically-stacked drive components** with air end mounted above the main motor reduce overall footprint, improve balance and simplify belt tensioning
- **Extended life consumables to 2,000 hours** reduces frequency of servicing
- **Common platform** accommodates fixed speed and variable speed drives (VSD) in same footprint
- **Quiet operation (69 dB(A))** complements the small footprint for installation and operation within limited workspaces

## Reliable, Precise Operation

- **New airend with integrated separation system** improves air/oil separation (<5 ppm) for peak air quality
- **Improved seals and fewer components** reduce the potential for leaks and increase reliability
- **Plug-in Danfoss drive** eliminates overheating and related component failures
- **IE3 energy-efficient fixed and variable speed motors** support continuous operation up to 46°C (115°F)
- **Improved cooler** design minimizes thermal expansion effects



The all-in-one CE55X airend features improved air/oil separation and reliability.



# Convenient Choices for a Complete AIR SOLUTION

## TAS – The Total Package

To meet the most comprehensive air requirements, our Ingersoll Rand R-Series compressors are available with a Total Air System (TAS) option. These complete compressor, cooler and dryer systems come with integrated controls, water separators, drain ports, filter and receiver tanks. For any capacity you need, let Ingersoll Rand provide the complete answer in a compact solution that fits your air requirements and your workspace!

- **High-efficiency filter and integrated dryer** deliver ISO 1-5-1 quality air up to 38°C (100°F)
- **Patented 3-in-1 heat exchanger** provides increased reliability and efficiency
- **Minimized installation costs**, single-point maintenance and monitoring
- **Environmentally friendly R407C refrigerant** provides class-leading low global warming potential index



TAS (Total Air System)

- A Patented 3-in-1 heat exchanger
- B High-efficiency filters
- C Condenser

- D R407C refrigerant
- E Cyclon water separator

Features Description	Fixed Speed	Variable Speed
Xe-Series 50 Controller	●	
Xe-Series 70 Controller	○	●
Xe-Series 70 controller with ECO module (United States only)		○
Total Air System (TAS) with integrated dryer	○	○
Power outage restart	○	○
Frost protection	○	
Residential filter		○
Outdoor modification enclosure	○	
Ultra FG or Ultra EL coolant	○	○
Hi-dust air filter	○	
Low voltage	○	○
Vibration Isolation System	●	●
Receiver tank size		
272/500 liter (Europe)	○	○
80/120 gallon (United States)	○	○

● Standard Feature ○ Optional Feature “Blank” Not Available



Ingersoll Rand – 50/60 Hz Performance

Table with 11 columns: Model, Max. Pressure (bar g, psig), Nominal Power (kW, hp), Capacity (FAD)\* (m³/min, cfm), Dimensions (mm, in), and Weight (kg, lb). Rows include models R4i, R4i TAS†, R5.5i, R5.5i TAS†, R7.5i, R7.5i TAS†, R11i, and R11i TAS†.

Ingersoll Rand Nirvana – 50/60 Hz Performance

Table with 11 columns: Model, Max. Pressure (bar g, psig), Nominal Power (kW, hp), Capacity (FAD) @ 10 barg (m³/min, cfm), Dimensions (Length x Width x Height) (mm, in), and Weight (Air-cooled) (kg, lb). Rows include models R5.5n, R7.5n, R11n, R5.5n TAS†, R7.5n TAS†, and R11n TAS†.

Table with 10 columns: Receiver Tank, Length mm, Width mm, Height mm, and Additional Mass (kg, lb). Rows include Europe (272 l and 500 l Tank-mounted Versions) and United States (80 gal and 120 gal Tank-mounted Versions).


\*FAD (Free Air Delivery) is full package performance including all losses. Tested per ISO 1217 : 2009 Annex C. and is measured at .5 bar/10 psi lower than maximum pressure on non-TAS units and at maximum pressure on TAS equipped units.

†TAS units deliver ISO Class 1-5-1 quality air measured at steady state conditions in accordance with ISO 8573-1:2001 that dictates inlet air to package of 25°C (77°F) and relative humidity of 60%.



ingersollrandproducts.com

Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a global business committed to a world of sustainable progress and enduring results.



Ingersoll Rand, IR, the IR logo are trademarks of Ingersoll Rand, its subsidiaries and/or affiliates.

Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service. R-Series compressors are intended for compressed air applications only. Ingersoll Rand assumes no responsibility or liability for compressors used in any application other than compressed air. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs, available functions and specifications are subject to change without notice or obligation.



mb air systems ltd

**Company Directory:**

149 Glasgow Road  
Wishaw  
Lanarkshire  
ML2 7QJ  
Tel 01698 355711  
Fax 01698 359299

Wellheads Road  
Farburn Industrial Estate  
Dyce, Aberdeen  
AB21 7HG  
Tel 01224 723434  
Fax 01224 723545

Fleming Close  
Segensworth East  
Fareham  
Hampshire  
PO15 5SB  
Tel 01489 588398  
Fax 01489 588381

8 Burford Way  
Boldon Business Park  
Boldon  
Tyne & Wear  
NE35 9PZ  
Tel 0191 519 5500  
Fax 0191 537 1105

E-mail [sales@mbairsystems.co.uk](mailto:sales@mbairsystems.co.uk)  
[www.mbairsystems.co.uk](http://www.mbairsystems.co.uk)  
[www.airwinch.co.uk](http://www.airwinch.co.uk)



engineering solutions

design product finishing pneumatics & tools  
compressed air service  
offshore lifting