



Compressor	7/26E+	7/31E+	7/41+
<b>GENERAL INFORMATION</b>			
Free Air Delivery - m <sup>3</sup> /min (cfm)	2.5 (90)	3.0 (105)	4.0 (141)
Rated Operating Pressure - bar (psi)	7.0 (100)	7.0 (100)	7.0 (100)
Maximum allowable pressure - bar (psi)	8.6 (125)	8.6 (125)	8.6 (125)
Safety valve setting - bar (psi)	10.0 (145)	10.0 (145)	10.0 (145)
<b>ENGINE</b>			
Make	Yanmar	Yanmar	Yanmar
Model	3IRH2NS	3IRH8N	4IRH8N
No. of cylinders	3	3	4
Full load speed - rpm	2800	2800	2800
Power - kW (HP)	21.2 (28.5)	26.0 (34.8)	34.8 (47.0)
Electrical - volts	12	12	12
Cooling	Water	Water	Water
Fuel tank capacity - litres	50	50	40
Air outlets BSPT (British Standard Pipe Thread)	2 x 3/4"	2 x 3/4"	2 x 3/4"
<b>SOUND LEVEL</b>			
Fully compliant to outdoor noise directive 2000/14/EC (2006) - L <sub>WA</sub>	98	98	98
<b>TYRES</b>			
Tyre size	155 R13	155 R13	155 R13
Number of wheels	2	2	2
<b>DIMENSIONS (WITH RUNNING GEAR)</b>			
Length (fixed height) - mm	2923	2923	3052
Length min/max (adjustable height) - mm	3213 / 3369	3213 / 3369	3322 / 3577
Width - mm	1390	1390	1390
Height - mm	1235	1235	1369
Ground clearance - mm	220	220	250
Weight (net) fixed/adjustable - kg	575 / 590	595 / 610	673 / 706
Weight (working) fixed/adjustable - kg	615 / 630	635 / 650	706 / 739
<b>DIMENSIONS (ON SHIPPING SUPPORT)</b>			
Length - mm	1764	1764	1785
Width - mm	940	940	940
Height - mm	1145	1145	1204
Weight (net) - kg	495	515	553
Weight (working) - kg	535	555	586
Generator option - add (kg)	53	53	53

### Tough Top

The optional "Tough Top" polymer canopy combines durability with aesthetic design, making these compressor models an especially attractive investment for everyday applications in the toughest working conditions.

As well as its outstanding durability, the Tough Top canopy is also non-corrosive. It can be supplied in customer colours and retrofitted to existing compressor units.



Side swing parking brake option



6 kVA generator option with enhanced control panel



Road lights with grille protection and banded base options

### Reduced risk

The 7/26E+, 7/31E+ and 7/41+ have an intuitive, simple key-start sequence, ideal for rental companies as there is a reduced risk of machine abuse by untrained operators. The user-friendly control panel offers an open layout of instruments and warning indicators.

Features include a lockable canopy and lockable steel instrument panel cover. In addition, by keeping the lifting eye within the compressor enclosure, the risk of theft is reduced.



Wide opening canopy for easy service access



6 kVA generator option



Variable height braked running gear option

### Options at will...

Highly modular design allows optional equipment to be easily added at the point of manufacture. The wide range of options available allow the machines to be adapted to the specific application, such as the fitting of an integral aftercooler system for abrasive blasting; or an onboard 6 Kva generator, to a personal color scheme in the company livery.

### Excellent serviceability with easy access to all maintenance points.

All areas have been carefully designed for ease of inspection, maintenance and repair. Service intervals for several components have been extended to increase uptime and reduce maintenance costs.

[www.doosanportablepower.com](http://www.doosanportablepower.com)



Portable Power

